








		Description	Model	Schedule Options			User Interface	Application												Power Method	Features and Functions															Service Reminders	Limited Warranty	Wiring Terminals		Accessories Included				
Wireless Communication				Program Options	Temporary Override	Permanent Hold	Vacation Hold		Stages	Gas, Oil or Electric	Heat Pump	750 Millivolt*	Linevolt	Selectable Residential and Light Commercial	Duel fuel	Balance Point Lockout	Upstage Timer & Droop Settings	Humidification Control	Dehumidification Control	Ventilation Control		Demand Response	Permanent Memory Retention	Selectable Auto or Manual Changeover	Auxiliary Heat Lockout	Adaptive Intelligent Recovery	Temperature Setpoint Limits	Keypad Lockout	Programmable & Circulation Fan	Tri-Lingual Language Options	Wireless Outdoor Sensor	Wired Outdoor Sensor	Wired Indoor Sensor	Wireless Indoor Temp/ Hum Sensor	Wireless Indoor Motion Sensor	Dealer Info On Screen	Display Size (Viewable)	Continuous Backlighting	Filter, Humidifier Pad, UV Lamp Replacement Reminders					
WiFi & RedLINK® 3.0		T10+ Thermostat, EIM, RATS/DATS, Wireless Indoor Sensor	YTHM1004R3000	Geofence, 7 day, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 4H/2C Heat Pump Up to 3H/2C Conventional	•	•	•		•	•	•	•	•	•	•	24 volt to R and C at thermostat and EIM	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	7.27 sq. in.	•	•	5 Year	Equipment Interface Module R, C, RH, RC, W, O/B, W2/AUX1, W3/AUX2, Y, Y2, G, L, U1, U1, U2, U2, U3, U3, S1, S1, S2, S2, S3, S3, S4, S4		T10+ Thermostat, THM04R3000 EIM, 2 duct sensors, C7189R300 Wireless Indoor Sensor	
		T10+ Thermostat, EIM, RATS/DATS, Wireless Indoor Sensor, Wireless Outdoor Sensor	YTHM1004R3001	Geofence, 7 day, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 4H/2C Heat Pump Up to 3H/2C Conventional	•	•	•		•	•	•	•	•	•	•	24 volt to R and C at thermostat and EIM	•	•	•	•	•	•	•	•	•	•	•	•	•	•	7.27 sq. in.	•	•	5 Year	Equipment Interface Module R, C, RH, RC, W, O/B, W2/AUX1, W3/AUX2, Y, Y2, G, L, U1, U1, U2, U2, U3, U3, S1, S1, S2, S2, S3, S3, S4, S4		T10+ Thermostat, THM04R3000 EIM, 2 duct sensors, C7189R3002 Wireless Indoor Sensor, C7089R3013 Wireless Outdoor Sensor		
		T10+ Pro Smart with RedLINK® Sensor	THX321WFS3001W	Geofence, 7 day, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		•	•	•	•	•	•	•	C-Wire	•	•	•	•	•	•	•	•			•	•	•	•	•	7.27 sq. in.	•	•	5 Year	R, RC, C, W, W2-AUX, E, O/B, Y, Y2, G, L, K, U, U, S and S		C7189R3002 wireless temp/humidity/motion sensor, UWP wall plate, decorative cover plate, & mounting hardware	
		T10+ Pro Smart without Sensor	THX321WF3003W																																						UWP wall plate, decorative cover plate, & mounting hardware			
WiFi		T6 Pro Smart	TH6320WF2003	Geofence, 7-day, 5-1-1, 5-2, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		•	•	•	•			•	C-Wire	•	•	•	•	•	•	•	•		Via internet	Lockouts only, no display	•			5 Year	R, RC, C, W, W2-AUX, E, O/B, Y, Y2, G, L, K, U, U, S and S		UWP wall plate, decorative cover plate, & mounting hardware					
			TH6220WF2006	Geofence, 7-day, 5-1-1, 5-2, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 2 Heat/1 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		•	•	•	•			C-Wire	•	•	•	•	•	•	•	•	•		Via internet	Lockouts only, no display	•			5 Year	R, RC, C, W, W2-AUX, E, O/B, Y, Y2, G, L, K, S and S		UWP wall plate, decorative cover plate, & mounting hardware					
		FocusPRO® S200 Thermostat	TH2110WF4008	Geofence, 7-day, 5-1-1, 5-2, 1 week, no schedule	•	•	Through app	Soft Keys or Through App	1 Heat/1 Cool	•	•	•		•	•	•	•			C-Wire	•	•	•	•	•	•								4.84 sq. in.		Filter only	5 Year	R, Rc, C, W, Y, G, O/B, K, L/A		UWP wall plate, decorative cover plate with J-box adapter, & mounting hardware				
			TH2320WF4010	Geofence, 7-day, 5-1-1, 5-2, 1 week, no schedule	•	•	Through app	Soft Keys or Through App	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		•	•	•	•			C-Wire	•	•	•	•	•	•	•		Via internet	•			4.84 sq. in.		Filter only	5 Year	R, Rc, C, W, Y, Y2, G, O/B, K, W2-AUX, E, S, S, L/A		UWP wall plate, decorative cover plate with J-box adapter, & mounting hardware					
		9000 Smart	TH9320WF5003	7-Day or NP	•	•	•	Touchscreen	Up to 2 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		•	•	•	•			C-Wire	•	•	•	•	•	•	•	•	•		Via internet			8 sq. in.	•	Filter, humidifier pad only	5 Year	R, RC, C, W-O/B, Y, G, W2-AUX/E, Y2, L, K		Mounting hardware				
		Vision PRO® 8000 Smart	TH8321WF1001	7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		•	•	•	•	•	•	•	C-Wire	•	•	•	•	•	•	•	•		Via internet	•	•	•	10 sq. in.	•	•	5 Year	R, RC, W2-AUX/E, Y, Y2, G, C, K, S1, S1, W-O/B, U1, U1, A-L/A		Mounting hardware			
RedLINK® 1.0/2.0 Accessories		Prestige® IQA Kits	YTHX9421R5085WW	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	•	•	•		•	•	•	•	•	•	•	24 volt to R and C at thermostat and EIM	w/ Gateway	•	•	•	•	•	•	•	•	•	•	•	•	•	•	8 sq. in.	•	•	5 Year	Prestige IQA - R, C, Equipment Interface Module - R, C, RH, RC, W-O/B, W2/AUX1, W3/AUX2, Y, Y2, G, A-L/A, U1, U1, U2, U2, U3, U3, S1, S1, S2, S2, S3, S3, S4, S4 A, B, C, D		THM5421R1021 Equipment Interface Module and 2 duct sensors	
			YTHX9421R5101WW	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	•	•	•		•	•	•	•	•	•	•	24 volt to R and C at thermostat and EIM	w/ Gateway	•	•	•	•	•	•	•	•	•	•	•	•	•	•	8 sq. in.	•	•	5 Year	Prestige IQA - R, C, Equipment Interface Module - R, C, RH, RC, W-O/B, W2/AUX1, W3/AUX2, Y, Y2, G, A-L/A, U1, U1, U2, U2, U3, U3, S1, S1, S2, S2, S3, S3, S4, S4 A, B, C, D		THM5421R1021 Equipment Interface Module, C7089R1013 wireless outdoor sensor, and 2 duct sensor	
			YTHX9421R5127WW	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool –Heat Pump Up to 3 Heat/2 Cool –Conventional	•	•	•		•	•	•	•	•	•	•	24 volt to R and C at thermostat and EIM	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	8 sq. in.	•	•	5 Year	Prestige IQA - R, C, Equipment Interface Module - R, C, RH, RC, W-O/B, W2/AUX1, W3/AUX2, Y, Y2, G, A-L/A, U1, U1, U2, U2, U3, U3, S1, S1, S2, S2, S3, S3, S4, S4 A, B, C, D		THM5421R1021 Equipment Interface Module, THM6000R7001 RedLINK Internet Gateway and 2 duct sensors	
			YTHX9421R7001WW	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool –Heat Pump Up to 3 Heat/2 Cool –Conventional	•	•	•		•	•	•	•	•	•	•	24 volt to R and C at thermostat and EIM	•	•	•	•	•	•	•	•	•	•	•	•	•	•	8 sq. in.	•	•	5 Year	Prestige IQA - R, C, Equipment Interface Module - R, C, RH, RC, W-O/B, W2/AUX1, W3/AUX2, Y, Y2, G, A-L/A, U1, U1, U2, U2, U3, U3, S1, S1, S2, S2, S3, S3, S4, S4 A, B, C, D		THM5421R1021 Equipment Interface Module, THM6000R7001 RedLINK Internet Gateway, C7089R1013 wireless outdoor sensor, C7189R1004 wireless indoor sensor and 2 duct sensors		
		Prestige® IQA	THX9421R5021WW	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool –Heat Pump Up to 3 Heat/2 Cool –Conventional	•	•	•		•	•	•	•	•	•	•	24 volt to R and C at thermostat and EIM	w/ Gateway	•	•	•	•	•	•	•	•	•	•	•	•	•	8 sq. in.	•	•	5 Year	Prestige IQA - R & C. (EIM ordered separately)		Mounting hardware		
		RedLINK® VisionPRO® 8000	TH8110R1008	7-Day or NP	•	•	•	Touchscreen	1 Heat/1 Cool**	•	•	•		•	•	•					Dual powered (battery and hardware)	w/ Gateway	•	•	•	•	•	•	•	•	•	•	•	•	•	10 sq. in.	•	•	5 Year	R, RC, C, W-O/B, Y, G, K, S1, S1		Batteries & mounting hardware		
			TH8320R1003	7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•	•		•	•	•	•				Dual powered (battery and hardware)	w/ Gateway	•	•	•	•	•	•	•	•	•	•	•	•	•	•	10 sq. in.	•	•	5 Year	R, RC, C, W-O/B, W2-AUX/E, Y, Y2, G, A-L/A, K, S1, S1		Batteries & mounting hardware	
			TH8321R1001	7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•	•		•	•	•	•	•	•	•	Dual powered (battery and hardware)	w/ Gateway	•	•	•	•	•	•	•	•	•	•	•	•	•	10 sq. in.	•	•	5 Year	R, RC, C, W-O/B, W2-AUX/E, Y, Y2, G, A-L/A, K, U1, U1, S1, S1		Batteries & mounting hardware		
			YTH8321R1002	7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•	•		•	•	•	•	•	•	•	Dual powered (battery and hardware)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	10 sq. in.	•	•	5 Year	R, RC, C, W-O/B, W2-AUX/E, Y, Y2, G, A-L/A, K, U1, U1, S1, S1		RedLINK Internet Gateway, Batteries & mounting hardware		
		FocusPRO® 6000 RedLINK® Programmable Kit	YTH6320R1001	5-1-1/5-2	•	•		Soft Keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•	•		•	•	•	•				Batteries at thermostat. R and C at EIM		•	•	•	•	•				•					5.09 sq. in.			5 Year	Equipment Interface Module – C, R, RC, RH, W-O/B, W2-AUX/E, Y, Y2, G, L, RAS, RAS		EIM, Return Air Sensor, Batteries & mounting hardware		
		FocusPRO® 5000 RedLINK® Non-Programmable	YTH5320R1000	Non programmable				Soft Keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•	•		•	•	•	•				Batteries at thermostat. R and C at EIM		•	•	•	•	•				•					5.09 sq. in.			5 Year	Equipment Interface Module – C, R, RC, RH, W-O/B, W2-AUX/E, Y, Y2, G, L, RAS, RAS		EIM, Return Air Sensor, Batteries & mounting hardware		
Z-Wave®		T6 Pro Z-Wave	TH6320ZW2007	7-Day, 5-1-1, 5-2, 1 week no schedule, Z-Wave occupancy	•	•	Through Z-Wave app	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•	•		•	•	•	•				Dual powered (battery and hardware)		•	•	•	•	•	•	•	•			•	•		6.89 sq. in.	•	•	5 Year	C, R, RC, Y, Y2, G, O/B, W, W2, AUX, E, L, K, S and S		UWP wall plate, decorative cover plate, & mounting hardware		

*For 750 millivolt thermostats without EIM, 24 volt transformer must wire to Rc and C and heater wires to R and W. For EIM, 24 volts to R and C. Millivolt heater to Rh and W.

Non-Connected Thermostats

	Description	Model	Scheduling	User Interface	Application					Power Method				Sensors				Display Information		Limited Warranty	Wiring Terminals	Accessories Included
					Stages	Gas, Oil or Electric	Heat Pump	750 Millivolt*	Linevolt		Permanent Memory Retention	Selectable Auto or Manual Changeover	Dual Fuel	Wired Outdoor Sensor	Wired Indoor Sensor	Floor / Slab Sensor	Temperature Setpoint Limits	Display Size (Viewable)	On Demand Backlighting			
	T6 Pro	TH6320U2008	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•	•	Lockouts only, no display	•		•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, Y2, G, L, K, S and S, O/B, and E and S	UWP wall plate, decorative cover plate, mounting hardware & batteries
		TH6220U2000	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•	•	Lockouts only, no display	•		•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, Y2, G, L, K, S and S, O/B, and E and S	UWP wall plate, decorative cover plate, mounting hardware & batteries
		TH6210U2001	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•					•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, G, L, O/B, E and K	UWP wall plate, decorative cover plate, mounting hardware & batteries
	T6 Pro Hydronic	TH6100AF2004	7-day, 5-1-1, 5-2, or NP	Soft keys	1 Stage Hot Water Heat Only – No Fan					Dual powered (battery and hardwire)	•					•	•	5.44 sq. in.	•	5 Year	R, RC, C, W, S, and S	Floor sensor, UWP wall plate, decorative cover plate, mounting hardware & batteries
	FocusPRO® P200 Thermostat	TH2110U4004	7-day, 5-1-1, 5-2, 1 week, no schedule	Soft Keys	1 Heat/1 Cool	•		•		Dual powered (battery and hardwire)	•	•					•	4.84 sq. in.	•	5 Year	R, Rc, C, W, O/B, Y, G, L, and K	UWP wall plate, decorative cover plate with J-box adapter, mounting hardware & batteries
		TH2320U4006	7-day, 5-1-1, 5-2, 1 week, no schedule	Soft Keys	Up to 3 Heat/2 Cool - Heat Pump Up to 2 Heat/2 Cool - Conventional	•	•	•		Dual powered (battery and hardwire)	•	•	•	•			•	4.84 sq. in.	•	5 Year	R, Rc, C, W, O/B, Y, Y2, G, W2-AUX, E, S, S, L, and K	UWP wall plate, decorative cover plate with J-box adapter, mounting hardware & batteries
	T4 Pro	TH4210U2002	7-day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•					•	3.93 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, G, L, O/B, E & K	UWP wall plate, decorative cover plate, mounting hardware & batteries
		TH4110U2005	7-day, 5-1-1, 5-2, or NP	Soft keys	Up to 1 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•					•	3.93 sq. in.	•	5 Year	R, RC, W, O/B, Y, G, C, L, and K	UWP wall plate, decorative cover plate, mounting hardware & batteries
	TL8100 Hydronic	TL8100A1008	7-Day	Soft keys	Control a line Voltage (120/240VAC) valve or pump or a 24 volt valve	Gas or oil			•	Battery powered	•							2.67 sq. in.	•	5 Year	1, 2, 3	Mounting hardware & batteries
	FocusPRO® N100 Thermostat	TH1110U4000	No Schedule	Soft Keys	1 Heat/1 Cool	•	•	•		Dual powered (battery and hardwire)	•	•					•	4.09 sq. in.		5 Year	R, Rc, C, W, O/B, Y, G, L and K	UWP wall plate, decorative cover plate with J-box adapter, mounting hardware & batteries
		TH1320U4002	No Schedule	Soft Keys	Up to 3 Heat/2 Cool - Heat Pump Up to 2 Heat/2 Cool - Conventional	•	•	•		Dual powered (battery and hardwire)	•	•	•	•			•	4.09 sq. in.		5 Year	R, Rc, C, W, O/B, Y, Y2, G, W2-AUX, E, S, S, L, and K	UWP wall plate, decorative cover plate with J-box adapter, mounting hardware & batteries
	T3 Pro Non-Programmable	TH3210U2004	NP	Soft keys	2 Heat/1 Cool–Heat Pump 1 Heat/1 Cool–Conventional	•	•	•		Dual powered (battery and hardwire)	•	•					•	3.32 sq. in.	•	5 Year	R, RC, C, W, O/B, Y, G, AUX, and E	UWP wall plate, decorative cover plate, mounting hardware & batteries
		TH3110U2008	NP	Soft keys	1 Heat/1 Cool–Heat Pump 1 Heat/1 Cool–Conventional	•	•	•		Dual powered (battery and hardwire)	•	•					•	3.32 sq. in.	•	5 Year	R, RC, C, W, O/B, Y, and G	UWP wall plate, decorative cover plate, mounting hardware & batteries
	Pro 3000 Non-Programmable	TH3210D1004	NP	Soft keys	2 Heat/1 Cool –Heat Pump only		•			Dual powered (battery and hardwire)	•	Manual						1.32 sq. in.	•	5 Year	R, C, O, B, Y, G, L, AUX, and E	Mounting hardware & batteries
		TH3110D1008	NP	Soft keys	1 Heat/1 Cool –Heat Pump 1 Heat/1 Cool –Conventional	•	•	•		Dual powered (battery and hardwire)	•	Manual						1.32 sq. in.	•	5 Year	R, RC, C, O, B, Y, W, and G	Mounting hardware & batteries
	T1 Pro Non-Programmable	TH1110D2009	NP	Soft keys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	Manual					•	2.37 sq. in.	•	5 Year	C, R, RC, W, O/B, Y, G	UWP wall plate, decorative cover plate, mounting hardware & batteries
	E1 PRO Non-Programmable	TH1110E1000	NP	Soft keys	1 Heat/1 Cool –Heat Pump 1 Heat/1 Cool –Conventional	•	•	•		Dual powered (battery and hardwire)	•	Manual						3.32 sq. in.	•	2 Year	R, RC, C, W, Y, G, O, and B	Wall-plate, mounting hardware, & batteries
	The Round™	T87K1007	NP	Dial	1 Heat or 1 Cool	•				Power stealing							50010944-001	N/A		5 Year	R, W, Y	Mounting hardware
		T87N1000	NP	Dial	1 Heat/1 Cool	•				Power stealing		Manual					50010944-001	N/A		5 Year	R, RC, W, Y, G, O, B	Mounting hardware
		T87N1026	NP	Easy-To-See™	1 Heat/1 Cool	•				Power stealing		Manual					50010944-001	N/A		5 Year	R, RC, W, Y, G, O, B	Mounting hardware
	Econostat Horizontal	T8034N1007	NP	Slide switches and lever	1 Heat/1 Cool	•				Mechanical		Manual					50019661-001	N/A		5 Year	R, RC, W, Y, G, O, B	Mounting hardware
	Econostat	T822K1000	NP	Slide switches and lever	1 Heat	•				Mechanical		Positive off					50019661-001	N/A		5 Year	R, W	Mounting hardware
		T827K1009	NP	Slide switches and lever	1 Heat	•		•		Mechanical		Positive off					50019661-001	N/A		5 Year	R, W	Mounting hardware
	TL8230	TL8230A1003	7-Day	Soft keys	1 Heat				•	3328 watts @ 208 VAC Max 3840 watts @ 240 VAC Max	•	Positive off						2.67 sq. in.	•	5 Year	4-wire DPST	Mounting hardware
	LineVoltPRO™	TL7235A1003	NP	Horizontal lays	1 Heat				•	3600 watts @240 VAC Max 3120 watts @208 VAC Max	•	Positive off						2.67 sq. in.	•	3 Year	4-wire DPST	Mounting hardware
	T410A,B Line Voltage Electric Heat	T410A1013 T410A1021 T410B1004	NP	Dial	1 Heat				•	22A @ 120/208/240 VAC Max, 19A @ 277 VAC Max		T410B has positive off					272804A Range Stop and Loading Cover	N/A		3 Year	T410A - 2-wire SPST T410B - 4-wire DPST	Mounting hardware
	Line Volt 5-2 Programmable	TH105PLUS	5-2	Buttons	1 Heat				•	3500 watts @240 VAC Max 1700 watts @120 VAC Max	•						•		•	3 Year	2-wire SPST	Mounting hardware